



Index:

Hose Reels..... 64-65
FRL-Units 66
Valves, Blow gun and Tyre inflator 67
Quick Connectors..... 68



Spring operated Hose Reels

Part.No

Series ORK, ORM

Open hose reel.

	Length m	Diameter mm-inch	Conn. threads	Work. Pressure		
				MPa	bar	
Series ORK	10	10 - 3/8"	G3/8" (f)	1,5	15	44231
Series ORM	15	12,5 - 1/2"	G1/2" (f)	1,5	15	44241



Series ORS

Open hose reel.

	Length m	Diameter mm-inch	Conn. threads	Work. Pressure		
				MPa	bar	
Series ORS	15	10 - 3/8"	G3/8" (f)	1,5	15	744220
Series ORS	15	12,5 - 1/2"	G1/2" (f)	1,5	15	744230



Series OR

An open hose reel with longer hose lengths. If mounted to the ceiling the hose guide must be located to give correct hose direction. The hoses are fitted with swaged couplings.

	Length m	Diameter mm-inch	Conn. threads	Work. Pressure		
				MPa	bar	
Series OR	20	12,5 - 1/2"	G1/2" (f)	1,5	15	44240



Series CRM

Medium sized enclosed hose reel.

The hose reel can be mounted to the ceiling, the wall or the floor. The wall bracket can easily be moved to fit other installations.

	Length m	Diameter mm-inch	Conn. threads	Work. Pressure		
				MPa	bar	
Series CRM	15	10 - 3/8"	3/8" (m)	1,5	15	944220
Series CRM	10	12,5-1/2"	1/2" (m)	1,5	15	944230



More information in the Hose reel section!

Spring operated Hose Reels

Part.No

Series CR

Enclosed hose reels. The hose reel can be mounted to the ceiling, the wall or the floor. The wall bracket can easily be moved to suit other installations. All hoses have swaged couplings.

	Length	Diameter	Conn. threads	Work. Pressure		Part.No
	m	mm-inch		MPa	bar	
Series CR	15	10 - 3/8"	G3/8" (m)	1,5	15	44220
Series CR	10	12,5-1/2"	G1/2" (m)	1,5	15	44230

**Series CRS**

Enclosed hose reels for air, supplied complete with a pivoting wall bracket. Hoses are fitted with swaged couplings.

	Length	Diameter	Conn. threads	Work. Pressure		Part.No
	m	mm-inch		MPa	bar	
Series CRS	12	8 - 5/16"	G1/4" (m)	2	20	44205
Series CRS	15	8 - 5/16"	G1/4" (m)	2	20	44206
Series CRS	10	10 - 3/8"	G3/8" (m)	2	20	44210



For the complete range of hose reels see the hose reel section!

Air Treatment Units (FRL)

Part.No

Air Treatment Units

These air treatment units combine the best of design with proven materials and production methods. They can handle air flows up to 900 l/min. Material: Zinc. Volume 40 cm³ (filter/regulator), 50 cm³ (lubricator), max working pressure 1,2 MPa (12 bar), temp. +5° to +60°C

Description	Conn. thread	Consist of:	Part.No
Air treatment unit, complete, assembled	G1/4" (f)	42107, 42108, 42009, 42112	42105
Air treatment unit	G1/4" (f)	42107, 42108, 42112	42104
Air treatment unit	G1/4" (f)	42107, 42009, 42112	42103



Shut-off valve

Shut-off valve with downstream air bleed. Material: Brass.

Description	Conn. thread	Max working pressure	Part.No
Shut-off valve	G1/4" (f)	1 MPa (10 bar)	42009



Filter-regulator

Filter-regulator 0-1 MPa, lockable, two stage filtration, 5 µm filter element. Material: Zinc

Description	Conn. thread	Volume	Max working pressure	Temp	Part.No
Filter-regulator	G1/4" (f)	40 cm ³	1,2 MPa (12 bar)	+5 to +60°C	42107



Lubricator

Air line lubricator with fill port and adjustment knob. Material: Zinc.

Description	Conn. thread	Volume	Max working pressure	Temp	Part.No
Lubricator	G1/4" (f)	50 cm ³	1,2 MPa (12 bar)	+5 to +60°C	42108



Accessories

Description	Part.No
Wall bracket, for filter-regulator (Part No 42107)	42110
Pressure gauge, ø 40 mm, 0-1,6 MPa (0-16 bar), Conn. thread G1/8" (m)	42112
Adapter, G 1/8" (m)	301296



Shut-off valves, Blow Gun

Part.No

Shut-off valves

Ball-valves made of brass with PTFE-seals, long or short levers, intended for oil and air lines.

Description	Conn. thread (f)	PN	Lever	Part.No
7640-3/8	G3/8"	6,4 MPa (64 bar)	Long	30101117
7640-1/2	G1/2"	6,4 MPa (64 bar)	Long	30101093
7640-3/4	G3/4"	4,0MPa (64 bar)	Long	30101111
7640-1	G1"	4,0 MPa (40 bar)	Long	30101081
7640-1-1/4	G 1 1/4"	2,5 MPa (25 bar)	Long	30101087
7640-1-1/2	G 1 1/2"	2,5 MPa (25 bar)	Long	30101084
7640-2	G2"	2,5 MPa (25 bar)	Long	30101102
7641-1/4	G1/4"	6,4 MPa (64 bar)	Short	30101129
7641-3/8	G3/8"	6,4 MPa (64 bar)	Short	30101144
7641-1/2	G1/2"	6,4 MPa (64 bar)	Short	30101123
Needle valve	G1/4"	2,5 MPa (25 bar)	Knob	28513



28513

Blow gun

Blow gun for efficient cleaning, made of impact resistant plastic with ergonomically designed handle. Tube length approx. 100 mm.

Description	Conn. thread	Weight (approx.)	Part.No
Blow gun	G1/4" (f)	100 g	44503

**Tyre inflator**

For connection to a pneumatic line. The pressure gauge 0,7 -10 bar (10 - 170 psi), is protected by a rubber cover. Delivered with 0,3 m hose and air nozzle.

Description	Conn. thread	Weight (approx.)	Part.No
Tyre inflator	G1/4" (f)	850 g	44635

**Tyre inflator, heavy duty**

For connection to pneumatic line. Delivered with a hose and air nozzle.

Description	Conn. thread	Hose length	Pressure range	Weight (approx.)	Part.No
Tyre inflator, cars	G1/4" (f)	0,5 m	0-9,6 bar	1 200 g	44634
Tyre inflator, trucks	G1/4" (f)	2,0 m	3-21 bar	1500 g	44636

**Air Line Hoses**

To connect the pump air motor to an air ring main. Made of armoured PVC, max. working pressure 1,5 MPa (15 bar), swaged couplings; one with swiveling nut and connection adapter (male/male).

Description	Hose Diameter	Length	Conn. thread	Part.No
Air line hose	1/4" i.d.	1,5 m	G1/4"(m)	48001
Air line hose	1/4" i.d.	3 m	G1/4"(m)	480013M
Air line hose	3/8" i.d.	1,5 m	G3/8"(m)	48002
Air line hose	3/8" i.d.	1,5 m	G3/8"(m)	480023M
Air line hose	1/2" i.d.	2,0 m	G1/2"(m)	48017



48001

Quick-couplings

Quick-couplings for Compressed Air

Hose Adapters

Hose Ø	Part No
1/4"	48510
5/16"	48511
3/8"	48512



Quick-Coupling

Thread	Part No
G1/4" (f)	44516



Nipples

Thread	Part No
R1/8" (m)	48500
R1/4" (m)	48501
R3/8" (m)	48502



G1/4" (f)	48503
G3/8" (f)	48504

Hose Adapters

Hose Ø	Part No
1/4"	48540
5/16"	48541
3/8"	48542
1/2"	48543



Quick-Coupling

Thread	Part No
G3/8" (f)	44521



Hose Connector

Hose Ø	Part No
1/4"	48520
5/16"	48521
3/8"	48522

Hose Adapters

Hose Ø	Part No
1/4"	48603
3/8"	48600
1/2"	48601
3/4"	48602



Quick-Coupling

Thread	Part No
G1/2" (f)	44531



Nipples

Thread	Part No
R1/4" (m)	48594
R3/8" (m)	48530
R1/2" (m)	48590
R3/4" (m)	48592



G3/8" (f)	48531
G1/2" (f)	48591

Hose Connector

Hose Ø	Part No
1/4"	48550
5/16"	48551
3/8"	48552
1/2"	48553



44626

Safety-Coupling ORION, connection 1/4", for Compressed Air