



Index:

Electrical Diesel Pumps.....84
Hose Reels, Funnels.....85
AdBlue.....85



Electric Diesel Pumps		Part.No
Wall Mounted Pump Kit 220V- 70 l/min 70 l/min pump mounted on a bracket for wall or tank mounting. The unit includes a 220 V diesel pump with on/off switch and 1.8 m cable, wall bracket, 4 m delivery hose, automatic nozzle and a three digit meter, flange mounted to the pump. Fluid inlet connection: 1" BSP (F). Meter valid for non commercial applications only.		53700 
Wall Mounted Pump Kit 220V- 50 l/min 50 l/min pump mounted on a bracket for wall or tank mounting. The unit includes a 220 V diesel pump with on/off switch and 1.8 m cable, wall bracket, 4 m delivery hose, aluminium nozzle and a three digit meter, flange mounted to the pump. Fluid inlet connection: 1" BSP (F). Meter valid for non commercial applications only.		53701 
Diesel Transfer Pump Kit 220V- 50 l/min 220 V AC diesel transfer pumps equipped with 4 m delivery hose, aluminium delivery nozzle and 2 m cable.		53710 
Diesel Transfer Pump Kit 24V- 40 l/min 24 V diesel transfer pumps equipped with 4 m x Ø 19 mm delivery hose, aluminium delivery nozzle and 2 m cable with alligator clamps..		53711 
Diesel Pump Accessories		
Description Diesel meter	Information 100 l/min. Reliable, easy to install and simple to calibrate. G1" (f) and inlet and outlet, both with flange for flange mounted applications. Maximum pressure: 10 Bar. Flow range: 10 to 100 l/minute. Precision after calibration: ± 1%. Meter valid for non commercial applications only.	23600 
Automatic nozzle	Fluid inlet: G1 " (f). Maximum delivery: 45 l/min.	23605 
Manual nozzle	Fluid inlet: G1 " (f). Maximum delivery: 100 l/min. Includes inlet swivel and lockable trigger.	23606 
Inlet swivel	For G1" (f) nozzles. Inlet/outlet threads: G1" (f).	23607 
Spare vanes	for the Diesel pumps	2446080
Suction hose.	Ø 25 mm x 4 m suction hose with foot valve. G1" (m)	28321
Suction attachment	with telescopic suction tube - 1000/1800 mm. G1" (m), G2" bung adaptor and foot valve with filter.	23609 

Spring Operated Hose Reels for Diesel						Part.No
Series ORK						
Open hose reel with a steel braided hydraulic hose, fitted with swaged couplings.						
	Length	Diameter	Conn. threads	Working Pres.		
	m	mm-inch		MPa	bar	
Series ORK	6	19-3/4"	G3/4" (f)	7,5	75	24472
						
Series ORL						
Heavy duty open hose reel with longer hose lengths, fitted with swaged couplings.						
	Length	Diameter	Conn. threads	Working Pressure		
	m	mm-inch		MPa	bar	
Series ORL	15	19-3/4"	G3/4" (f)	7,5	75	24932
						
Series LOR						
Open hose reel with steel braided, oil resistant rubber hose.						
	Length	Diameter	Conn. threads	Working Pressure		
	m	mm-inch		MPa	bar	
Series LOR	20	19-3/4"	G3/4" (f)	6	60	24943
Series LOR	15	25 - 1"	G1" (f)	6	60	24945
						
Series CRM						
A medium sized enclosed hose reel. The hose reel can be mounted on the ceiling, the wall or the floor. The wall bracket can easily be moved to fit other installations.						
	Length	Diameter	Conn. threads	Working Pressure		
	m	mm-inch		MPa	bar	
Series CRM	6	19-3/4"	G3/4" (f)	7,5	75	24492
						
Anti-splash funnel						
Description						
Ø 190mm funnel with anti-splash rim, filter and flexispout.						21632
Ø 230mm funnel with anti-splash rim, filter and flexispout.						21605
						
Garage Funnel						
Description						
300mm garage funnel with filter.						21606
300mm garage funnel c/w diesel/water separator filter.						21607
						

AdBlue Pumps & Spring Operated Hose Reels Part.No

Air Operated Drum Pump

Manufactured of Polypropylene and Polyethylene with EPDM sealings. Delivered with telescopic suction tube with G2" drum adapter and 2 m delivery hose with outlet valve.

Description	Suction tube Length	Suction tube diam.	Capacity (approx.)
Air operated drum pump	480 - 950 mm	ø27 mm	20 l/min

22049



Hand Operated Drum Pump

Manufactured of Polypropylene and Polyethylene with EPDM sealings. Delivered with telescopic suction tube with G2" drum adapter and 2 m delivery hose with outlet valve.

Description	Suction tube Length	Suction tube diam.	Capacity (approx.)
Hand operated drum pump	480 - 950 mm	ø27 mm	0,3 l/stroke

21029



Rotary Pump

Rotary pump made of polypropylene with ø27 mm outlet pipe and G2" (m) bung adapter.

Description	Suction tube length tube in 3 sections	Suction tube diam.	Capacity (approx.)	Weight (approx.)
Rotary pump	ø 44 mm	0,3 l/turn	1,8 kg	

21200



Series OR

Open stainless steel hose reel with longer hose lengths, fitted with stainless steel swaged couplings.

	Length m	Diameter mm-inch	Conn. threads
Series OR	20	12,5 - 1/2"	G1/2" (f)

24971



Series CRM

Enclosed hose reel with stainless steel swivel and swaged fittings. The hose reel can be mounted on the ceiling, the wall or the floor. The wall bracket can easily be moved to fit other installations.

	Length m	Diameter mm-inch	Conn. threads
Series CRM	10	12,5-1/2"	G1/2" (f)

924971



Drum Adapters and Accessories

Description	Information	
Adapter	G2" (f) -Trisure ø 55 mm, pitch approx. 4 mm (m)	28235
Adapter	G2" (f) -Multi adapter with locking screw ø55-65 mm(f)	28236
Adapter	G2" (f) -Midland	28234
Adapter	G2" (f) - Mauer ø 68 mm, pitch approx. 6 mm (m)	28238
Adapter	G2" (f) - Berg ø 53 mm, pitch approx. 3,5 mm (f)	28239
Adapter	G2" (f) - DIN 70 (f)	2310035
Adapter	G2" (f) - Mobil 20 l container	2310034
Adapter	G3/4" (f) - Trisure ø 55 mm, pitch 4 mm (m)	2310037
Adapter	G3/4" (f) - DIN 70 (f)	2310038
Suction Tube	Telescopic, length max 1100 mm (for IBC)	2410031
Hose	2 m, with shut off valve	28400

