

# GREASE FILLING PUMPS FOR CENTRAL LUBRICATION SYSTEMS

#### **GENERAL**

Hand operated filling pump for efficient and spill free filling of grease in central lubrication systems. Eliminates the mess normally associated with grease handling. Capacity: approx. 50 gr (1.8oz) per stroke. A wide range of accessories are available, such as hooks for when using plastic containers which normally can't be used with a drum lid. There is also a range of filling adapters for re-filling grease guns directly meaning that the use of cartridges is eliminated and all the mess that is associated with changing them.

Our grease filling pumps are divided into two main categories:

### **HEAVY DUTY MODEL**

- Heavy-duty, for daily operation and harsh environments.
- Follower plate and quick coupler is included.
- Choose the right model below depending on the container size.

### STANDARD MODEL

- Standard duty, less frequent use
- Follower plate and quick coupler is ordered separately.
- Choose the right model below depending on the container size.





| PART NO              | 11238     | 11237       | 11239    | 11236     |
|----------------------|-----------|-------------|----------|-----------|
| Suitable container:  | 5 kg      | 15-18 kg    | 25 kg    | 50 kg     |
|                      | (11 lbs)  | (33-39 lbs) | (55 lbs) | (110 lbs) |
| Container size: (mm) | 195-212   | 240-300     | 312-342  | 365-415   |
| (Inch)               | (7.6-8.3) | (9.4-11.8)  | (12.2-   | (14.4-    |
|                      |           |             | 13.4)    | 16.3)     |

| PART NO             | 11713                            | 11714             | 11715              |
|---------------------|----------------------------------|-------------------|--------------------|
| Suitable container: | 12-18 kg<br>(26-39 lbs)          | 20 kg<br>(44 lbs) | 50 kg<br>(110 lbs) |
| Container size:     | See follower plates on next page |                   |                    |

## **ACCESSORIES**

| PART NO        | DESCRIPTION  |                  |
|----------------|--|------------------|
| 1385111        | T-screws for 1171X  Mounts to the follower plate and allows for the use of plastic buckets.  |                  |
| 1385112        | T-screws for 1123X  Mounts to the follower plate and allows for the use of plastic buckets.  | <b>*****</b> 111 |
| 1115650        | T-adapter-kit  Mounts on the pump outlet, allowing pumps and screw tubes to be re-filled with the same pump, without having to the remove the outlet hose.               |                  |
| 18103          | Loader nipple Ø12mm (0.47")  Mounts to T-adapter-kit 1115650 for re-filling of grease guns with a Ø12mm filling nipple.  |                  |
| 18105          | Loader nipple Ø9mm (0.35")  Mounts to T-adapter-kit 1115650 for re-filling of grease guns with a Ø9mm filling nipple.  |                  |
| 14713          | Adapter for MLS (Lube-Shuttle®) screw cartrdige  Mounts to T-adapter-kit 1115650 for re-filling of MLS (Lube-Shuttle®) screw-in type cartridges.                         |                  |
| 1315656        | Dust cover for MLS Adapter Protects the MLS Adapter 14713 from dust and other particles being mixed in the grease, possibly incurring damage to machinery and equipment. |                  |
| 1315630        | Empty MLS (Lube-Shuttle®) cartridge For filling cartridges from grease kegs or buckets.  |                  |
| 55500206       | Quick Coupler Male G 3/8" (F) ISO 7241-1 series A equivalent, "Snap-Tite".   |                  |
| 55500306       | Quick Coupler Female G 3/8" (F) ISO 7241-1 series A equivalent, "Snap-Tite". Only for 11713.   |                  |
|                | Follower plate Only for 11713, 11714, 11715  |                  |
| 18569          | For 12,5 kg (27 lbs) 230-260 mm (9.1"-10.2")   |                  |
| 18570<br>18575 | For 18-20 kg (39-44 lbs) 260-290 mm (10.2"-11.4") For 50 kg (110 lbs) 300-330 mm (11.8"-13")   |                  |
| 18575          | For 50 kg (110 lbs) 300-330 mm (11.8"-13") For 50 kg (110 lbs) 340-360 mm (13.4"-14.2")  |                  |
| 18572          | For 50 kg (110 lbs) 360-395 mm (14.2"-15.6")   |                  |
| 10372          | [ 1 01 00 kg (110 lbs)   |                  |

